

Industry

Description

Technology:	Thermal transfer / Direct thermal
Print Head:	Edge Type
Print Width:	10 to 213 mm
Print Length:	5,5 to 1705 mm
Backing paper wide:	225 mm
Resolution:	305 dpi (12 dot)
Print speed:	up to 203 mm/sec (8 ips)
Ribbon saver	standard
Memory capacity:	16 MB SD-RAM, 16 MB flash ROM
Barcodes:	JAN8, EAN8, JAN13, EAN13, UPC-A, UPC-E, NW-7, CODE39, ITF, MSI, CODE93, CODE128, EAN128, INDUSTRIAL 2 of 5, POSTNET, u.s.w.
Codes 2D :	DataMatrix, MAXI code, PDF417, QR code, MicroPDF, CP code, RSS
Interface:	Parallel, USB 2.0, 10/100 MBit int. LAN Interface
Dimensions:	417 (W) x 395 (H) x 282 (D) mm
Options:	Cutter, Peel off module, Wireless LAN-, Start-Stop-, RS-232 Interface, Real time clock, RFID, Metal supply cover
Weight:	29 kg (without media and ribbon)

Consumables

Core diameter (Inside):	76,2 mm
Roll outside diameter:	200 mm (Inside winding)
Material thickness:	0,1 - 0,17 mm
Ribbon length:	max. 300 m



NEW

B-SX8